

■ Model No. **HP-180N**

Length : 320 mm

Weight : 3.7 kgs

■ Specifications:

Max. Pressure : 590 bar

Oil Required : 175 cc

■ Oil Delivery:

0.9 cc / stroke

■ Features:

- Ideal for our PNST-10 punch driver or any small remote heads requiring less than 180 cc oil volume.
- Bladder type oil reservoir allows operation in any position.
- Single stage pumping action.
- Not equipped with a relief valve.

■ Accessories:

1M hydraulic hose attached



Note:

This pump does NOT have a relief valve. It can not be used with compression heads requiring a relief valve to ensure a constant compression.



■ Model No. **HYP-700FT**

Length : 720 mm

Weight : 12.0 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 1000 cc

■ Oil Delivery:

35.8 cc / stroke at low pressure

2.1 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action.
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable foot hydraulic pump.

■ Accessories:

2M hydraulic hose attached



■ Model No. **HYP-700FTG**

Length : 720 mm
Weight : 12.6 kgs

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 1000 cc

■ Oil Delivery:

35.8 cc / stroke at low pressure
2.1 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action.
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable hydraulic foot pump.
- Attached with pressure gauge for pressure display.

■ Accessories:

2M hydraulic hose attached



● Pressure Gauge

※ Steel case colour for reference only.



MANUAL
Follow User Guide

MAINTAIN
Inspect Regularly

PROTECTION
Put On Goggles

PROTECTION
Work With Gloves

■ Model No. HP-700A

Length : 595 mm

Weight : 9.0 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 720 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure

2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable hydraulic hand pump.

■ Accessories:

2M hydraulic hose attached



■ Model No. **HP-700AG**

Height : 647 mm
Weight : 9.6 kgs

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 720 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure
2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action.
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable hydraulic hand pump.
- Attached with pressure gauge for pressure display.

■ Accessories:

2M hydraulic hose attached



● Pressure Gauge



■ Model No. HF-700

Length : 694 mm

Weight : 9.4 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 720 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure

2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action.
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable hydraulic hand pump.
- To comply with ergonomic design for hand and feet use.

■ Accessories:

2M hydraulic hose attached



■ Model No. HF-700G

Height : 656 mm
Weight : 10.0 kgs

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 720 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure
2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action.
- External adjustable pressure setting up to 700 bar.
- Internal oil bladder type oil reservoir allows operation in any position.
- Replaceable dropout bypass valve cartridge for easy repair.
- Economical yet dependable hydraulic hand pump.
- To comply with ergonomic design for hand and foot use.
- Attached with pressure gauge for pressure display.

■ Accessories:

2M hydraulic hose attached



● Pressure Gauge



■ Model No. **HP-30S**

Length : 600 mm

Weight : 15.6 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 3000 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure

2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance.
- Two stage pumping action .
- External adjustable pressure setting up to 700 bar.
- Economical yet dependable hydraulic hand pump.

■ Accessories:

2M hydraulic hose attached



■ Model No. **HP-30MD**

Length : 745 mm

Weight : 18.4 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 3000 cc

■ Oil Delivery:

12.26 cc / stroke at low pressure

2.26 cc / stroke at high pressure

■ Features:

- Dual speed pump piston for rapid advance
- Two stage pumping action
- External adjustable pressure setting up to 700 bar
- Economical yet dependable hydraulic hand pump
- Attached with pressure gauge for pressure display

■ Accessories:

Hydraulic hose should be ordered separately



●Pressure Gauge

